



vispronet

LIGHTBOX FLEX



INFORM
CREATE
ORDER

vispro
design



TABLE OF CONTENTS



vispronet[®]

EXHIBITION COUNTER LIGHTBOX FLEX	2
EXHIBITION WALL LIGHTBOX FLEX	4
EXHIBITION WALL LIGHTBOX FLEX CURVED	7
ACCESSORIES AND NOTES	9

EXHIBITION COUNTER LIGHTBOX FLEX



SACHSEN FAHNEN

vispronet®



- mobile trade fair counter made of plastic with a straight front
- practical click connectors, tool-free assembly
- bright, energy-saving Osram LED lighting
- modern and robust countertop

EXHIBITION COUNTER LIGHTBOX FLEX



System	<ul style="list-style-type: none"> · high-quality plastic frame with utility model protection (GM: 20 2019 103 837), white, V0 fire protection certification · Frame depth 120 mm · incl. feet · Osram LED components factory pre-assembled · wooden counter top (MDF board), black · for indoor use only · disassembled delivery 			
	Size B x H x T in cm	Weight system approx.	Total weight	Packaging dimensions
	85 x 100 x 35 cm	10,23 kg	15,73 kg	124 x 45,5 x 28,5 cm
	100 x 100 x 35 cm	11,15 kg	16,65 kg	124 x 45,5 x 28,5 cm
Print	<p>Finish</p> <ul style="list-style-type: none"> · Fitted all around with a flat piping for attachment to the frame <p>Material:</p> <ul style="list-style-type: none"> · One-sided printing: <ul style="list-style-type: none"> Print: polyester knitted fabric Lighttex SE, approx. 260 g/m² Back side: matt black (opaque) polyester knit (Multisol® X Opak SE, approx. 250 g/m²) · Double-sided printing: <ul style="list-style-type: none"> Polyester knitted fabric Lighttex SE, approx. 260 g/m² 			
Technical data	<ul style="list-style-type: none"> · Voltage: 24V, power: 96W · Current: 2A, luminous flux: 4000 lumens, light colour: cold white 			
Delivery content	<ul style="list-style-type: none"> · Print, system including counter top, trolley bag 			



All sizes are approximate. As we are constantly developing our products we reserve the right of changing technical issues and dimensional deviations.

EXHIBITION WALL LIGHTBOX FLEX



SACHSEN FAHNEN

vispronet®



- mobile, modular exhibition wall made of plastic with a straight front
- practical click connectors: tool-free assembly
- bright, energy-saving Osram LED lighting
- modularly expandable

EXHIBITION WALL LIGHTBOX FLEX



System	<ul style="list-style-type: none"> · High-quality plastic frame with utility model protection (GM: 20 2019 103 837), white, V0 fire protection certification · Frame depth: 120mm · incl. feet · Osram LED components factory pre-assembled · Wall or free-standing variant possible (different feet) · for indoor use only · Disassembled delivery 																														
Print	<p>Finish:</p> <ul style="list-style-type: none"> · Fitted all around with a flat piping for attachment to the frame <p>Material:</p> <ul style="list-style-type: none"> · One-sided printing: Print: polyester knitted fabric Lighttex SE, approx. 260 g/m² Back side: matt black (opaque) polyester knit (Multisol® X Opak SE, approx. 250 g/m²) · Double-sided printing: polyester knitted fabric Lighttex SE, approx. 260 g/m² 																														
Technical data	<table border="1"> <thead> <tr> <th></th> <th>Power Supply Mini</th> <th>Power Supply Midi</th> <th>Power Supply Maxi</th> </tr> </thead> <tbody> <tr> <td>Power</td> <td>96 W</td> <td>126 W</td> <td>152,4 W</td> </tr> <tr> <td>Current</td> <td>4 A</td> <td>5,25 A</td> <td>6,35A</td> </tr> <tr> <td>Voltage</td> <td></td> <td>24 V</td> <td></td> </tr> <tr> <td>Luminous flux</td> <td></td> <td>4000 Lumen</td> <td></td> </tr> <tr> <td>Light colour</td> <td></td> <td>cold white</td> <td></td> </tr> <tr> <td>Length of power cable with plug approx</td> <td></td> <td>ca. 280 cm</td> <td></td> </tr> </tbody> </table>				Power Supply Mini	Power Supply Midi	Power Supply Maxi	Power	96 W	126 W	152,4 W	Current	4 A	5,25 A	6,35A	Voltage		24 V		Luminous flux		4000 Lumen		Light colour		cold white		Length of power cable with plug approx		ca. 280 cm	
	Power Supply Mini	Power Supply Midi	Power Supply Maxi																												
Power	96 W	126 W	152,4 W																												
Current	4 A	5,25 A	6,35A																												
Voltage		24 V																													
Luminous flux		4000 Lumen																													
Light colour		cold white																													
Length of power cable with plug approx		ca. 280 cm																													
Delivery content	<ul style="list-style-type: none"> · Print, system, trolley bag 																														

All sizes are approximate. As we are constantly developing our products we reserve the right of changing technical issues and dimensional deviations.

EXHIBITION WALL LIGHTBOX FLEX



Size		System width										
		100 cm	185 cm	200 cm	285 cm	300 cm	385 cm	400 cm	485 cm	500 cm	585 cm	600 cm
System height 200 cm	Weight system ca.	11,25 kg	15,00 kg	15,54 kg	19,65 kg	20,19 kg	24,36 kg	24,90 kg	30,46 kg	31,00 kg	34,53 kg	35,07 kg
	Total weight	16,75 kg	20,50 kg	21,04 kg	25,15 kg	25,69 kg	35,36 kg	35,90 kg	41,46 kg	42,00 kg	45,53 kg	46,07 kg
	Packing dimensions	124 x 45,5 x 28,5 cm					2 Pakete je 124 x 45,5 x 28,5 cm					
System height 225 cm	Weight system ca.	12,09 kg	15,88 kg	16,42 kg	20,57 kg	21,11 kg	25,32 kg	25,86 kg	31,67 kg	32,21 kg	35,78 kg	36,32 kg
	Total weight	17,59 kg	21,38 kg	21,92 kg	26,07 kg	26,61 kg	36,32 kg	36,86 kg	42,67 kg	43,21 kg	46,78 kg	47,32 kg
	Packing dimensions	124 x 45,5 x 28,5 cm					2 Pakete je 124 x 45,5 x 28,5 cm					
System height 250cm	Weight system ca.	12,83 kg	16,66 kg	17,20 kg	21,39 kg	21,93 kg	26,18 kg	26,72 kg	32,81 kg	33,35 kg	36,96 kg	37,50 kg
	Total weight	18,33 kg	22,16 kg	22,70 kg	26,89 kg	27,43 kg	37,18 kg	37,72 kg	43,81 kg	44,35 kg	47,96 kg	48,50 kg
	Packing dimensions	124 x 45,5 x 28,5 cm					2 Pakete je 124 x 45,5 x 28,5 cm					



All sizes are approximate. As we are constantly developing our products we reserve the right of changing technical issues and dimensional deviations.

EXHIBITION WALL LIGHTBOX FLEX CURVED



SACHSEN FAHNEN

vispronet®



- mobile, modular exhibition wall made of plastic with a curved front
- practical click connectors: tool-free assembly
- bright, energy-saving Osram LED lighting
- modularly expandable

EXHIBITION WALL LIGHTBOX FLEX CURVED



Size		System width		
		100 cm	200 cm	300 cm
System height 200 cm	Weight system ca.	11,27 kg	15,58	20,95
	Total weight	16,77 kg	21,08	26,45
	Packing dimensions	124 x 45,5 x 28,5 cm		
System height 225 cm	Weight system ca.	12,11 kg	16,97	22,13
	Total weight	17,61 kg	22,47	27,63
	Packing dimensions	124 x 45,5 x 28,5 cm		
System height 250 cm	Weight system ca.	12,85 kg	17,24	22,91
	Total weight	18,35 kg	22,74	28,41
	Packing dimensions	124 x 45,5 x 28,5 cm		



System


- Curved high-quality plastic frame with utility model protection (GM: 20 2019 103 837), white, V0 fire protection certification
- Frame depth: 120 mm
- incl. feet
- Osram LED components factory pre-assembled
- For indoor use only
- Disassembled delivery

Print

- Finish:**
Cut all around and fitted with a flat piping for attachment to the frame
- Material:**
- One-sided printing:
Print : polyester knitted fabric Lighttex SE, approx. 260 g/m²
Back side: matt black (opaque) polyester knit (Multisol® X Opak SE, approx. 250 g/m²)
 - Double-sided printing:
Polyester knitted fabric Lighttex SE, approx. 260 g/m²

Technical data

	Power Supply Mini	Power Supply Midi	Power Supply Maxi
Power	96 W	126 W	152,4 W
Current	4 A	5,25 A	6,35 A
Voltage	24 V		
Luminous flux	4000 lumens		
Light colour	cold white		
Length of power cable with plug	ca. 280 cm		



Delivery content

- Print, system, trolley bag



ACCESSORIES



vispronet®

Base feet



Base feet with corner connectors, set of 2

- 2 feet made of powder-coated steel with corner connectors, white; plastic connector, white
- With corner connector
- Dimensions ca.:
40 x 10 x 10,3 cm (L x B x H)



Base feet without corner connectors, set of 2

- 2 feet made of powder-coated steel, white
- Without corner connectors
- Dimensions ca.:
40 x 10 x 0,7 cm (L x B x H)



One-sided base feet with corner connectors, set of 2

- 2 one-sided feet made of powder-coated layered steel with corner connectors, white; plastic connector, white
- With corner connectors on the right and left
- Dimensions ca.:
25 x 10 x 10,3 cm (L x B x H)



One-sided base feet without corner connectors, set of 2

- 2 one-sided feet made of powder coated steel, white
- Without corner ties
- Dimensions ca.:
25 x 10 x 0,7 cm (L x B x H)



Piping tool

- Practical tool for quick clamping of the print
- Robust plastic and steel
- Easy to use: simply press the textile print into the groove of the frame with the piping tool
- Size.: ca. 17,5 x 9,5 cm



Special gloves

- In the set: 2 pairs of special cotton gloves
- For gentle treatment of sensitive printed products, such as posters or signs
- Lint-free and washable
- Size: L



Connector clips, set of 10

- Connector clip set for the Lightbox Exhibition Wall Flex, consisting of 10 connector clips
- For connecting 2 or more Exhibition Walls Lightbox Flex
- Material: plastic, transparent

INFO



To prevent hairline cracks, avoid extreme temperatures and temperature fluctuations. Allow your package to reach room temperature before unpacking.



Be careful when installing the click connections - risk of finger crushing.



We assume no liability for improper assembly or use.



Avoid kinks when storing the prints



Only suitable for indoor use.

All sizes are approximate. As we are constantly developing our products we reserve the right of changing technical issues and dimensional deviations.